

UNOCAL PORSF
413.125101
05/15/89Product Name: UNOCAL GUARDOL MOTOR OIL 30
Product Code No: 03650XX30Page 1
Issue Date: 05/15/89**MANUFACTURER**UNOCAL REFINING & MARKETING DIVISION
UNION OIL COMPANY OF CALIFORNIA
1201 WEST 5TH STREET
LOS ANGELES, CALIFORNIA 90017CONTACT FOR FURTHER INFORMATION:
MSDS COORDINATOR 213-977-7589**Transportation Emergencies:**CHEMTREC
(800) 424-9300 Cont. U.S.
(202) 483-7616 (Collect)
from Alaska & Hawaii
Health Emergencies:
Call LOS ANGELES POISON
INFORMATION CENTER (24 hrs)
1-(800)-356-3129**PRODUCT IDENTIFICATION**

PRODUCT NAME: UNOCAL GUARDOL MOTOR OIL 30 *Heavy Duty*
SYNONYMS: UNION GUARDOL MOTOR OIL 30
GENERIC NAME: CRANKCASE OIL
CHEMICAL FAMILY: PETROLEUM HYDROCARBON
DOT PROPER SHIPPING NAME: NOT APPLICABLE
ID NUMBER: NONE
DOT HAZARD CLASSIFICATION: NOT REGULATED

SECTION I - COMPONENTS	PERCENT	EXPOSURE LIMIT	UNITS	AGENCY	TYPE
------------------------	---------	----------------	-------	--------	------

HAZARDOUS COMPONENTSSOLVENT DEWAXED DISTILLATE, HEAVY PARAFFIN
CAS #: 64742-65-0 63

5.000	MG/M3	OSHA	TWA
5.000	MG/M3	ACGIH	TWA
10.000	MG/M3	ACGIH	STEL

SOLVENT DEWAXED RESIDUAL OIL
CAS #: 64742-62-7 25

5.000	MG/M3	OSHA	TWA
5.000	MG/M3	ACGIH	TWA
10.000	MG/M3	ACGIH	STEL

PROPRIETARY ZINC COMPOUND
CAS #: PROPRIETARY

1.5 - 2.0

~NOT ESTABLISHED

OTHER COMPONENTSTRADE SECRET
CAS #: PROPRIETARY

10.0 - 10.5

NOT ESTABLISHED

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO THE REPORTING
REQUIREMENTS OF SARA 313 AND 40 CFR 372:

CAS NUMBER WEIGHT %

PROPRIETARY ZINC COMPOUND

PROPRIETARY 1.5-2.0

NOTE: THE IDENTITIES OF INGREDIENTS THAT ARE TRADE SECRETS ARE EXCLUDED FROM THIS LIST.

USEPA SF



1265443

UNION OIL CO.

Product Name: UNOCAL GUARDOL MOTOR OIL 30
Product Code No: 03650XX30

Page 2
Issue Date: 05/15/89

SECTION II - EMERGENCY AND FIRST AID PROCEDURES*****EMERGENCY*****

Have physician call LOS ANGELES POISON
INFORMATION CENTER (24 hrs) (800) 356-3129

EYE CONTACT:

IF IRRITATION OR REDNESS DEVELOPS, MOVE VICTIM AWAY FROM EXPOSURE AND INTO FRESH AIR. FLUSH EYES WITH CLEAN WATER. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION.

SKIN CONTACT:

WIPE MATERIAL FROM SKIN AND REMOVE CONTAMINATED SHOES AND CLOTHING. CLEANSE AFFECTED AREA(S) THOROUGHLY BY WASHING WITH MILD SOAP AND WATER AND, IF NECESSARY, A WATERLESS SKIN CLEANSER. IF IRRITATION OR REDNESS DEVELOPS AND PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION (BREATHING):

IF RESPIRATORY SYMPTOMS DEVELOP, MOVE VICTIM AWAY FROM SOURCE OF EXPOSURE AND INTO FRESH AIR. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. IF VICTIM IS NOT BREATHING, IMMEDIATELY BEGIN ARTIFICIAL RESPIRATION. IF BREATHING DIFFICULTIES DEVELOP, OXYGEN SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. SEEK IMMEDIATE MEDICAL ATTENTION.

INGESTION (SWALLOWING):

NO FIRST AID IS NORMALLY REQUIRED; HOWEVER, IF SWALLOWED, AND SYMPTOMS DEVELOP, SEEK MEDICAL ATTENTION.

COMMENTS:

NOTE TO PHYSICIANS: ACUTE ASPIRATION OF LARGE AMOUNTS OF OIL LADEN MATERIAL MAY PRODUCE A SERIOUS ASPIRATION PNEUMONIA. PATIENTS WHO ASPIRATE THESE OILS SHOULD BE FOLLOWED FOR THE DEVELOPMENT OF LONG-TERM SEQUELAE. REPEATED ASPIRATION OF SMALL QUANTITIES OF MINERAL OIL CAN PRODUCE CHRONIC INFLAMMATION OF THE LUNGS (I.E., LIPOID PNEUMONIA) THAT MAY PROGRESS TO PULMONARY FIBROSIS. SYMPTOMS OFTEN ARE SUBTLE AND RADIOLOGICAL CHANGES APPEAR WORSE THAN CLINICAL ABNORMALITIES. OCCASIONALLY, PERSISTENT COUGH, IRRITATION OF THE UPPER RESPIRATORY TRACT, SHORTNESS OF BREATH WITH EXERTION, FEVER AND BLOODY SPUTUM OCCUR. INHALATION EXPOSURE TO OIL MISTS BELOW CURRENT WORKPLACE EXPOSURE LIMITS IS UNLIKELY TO CAUSE PULMONARY ABNORMALITIES.

SECTION III - HEALTH HAZARDS/ROUTES OF ENTRY**EYE CONTACT:**

THIS MATERIAL MAY CAUSE MILD EYE IRRITATION. DIRECT CONTACT WITH THE LIQUID OR EXPOSURE TO VAPORS OR MISTS MAY CAUSE STINGING, TEARING AND REDNESS.

SKIN CONTACT:

THIS MATERIAL MAY CAUSE SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS, BURNING, AND DRYING AND CRACKING OF THE SKIN. NO HARMFUL EFFECTS ARE EXPECTED FROM SKIN ABSORPTION OF THIS MATERIAL. PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS MATERIAL.

INHALATION (BREATHING):

WHILE THIS MATERIAL HAS A LOW DEGREE OF TOXICITY, BREATHING HIGH CONCENTRATIONS OF VAPORS OR MISTS MAY CAUSE IRRITATION OF THE NOSE AND THROAT.

INGESTION (SWALLOWING):

WHILE THIS MATERIAL HAS A LOW DEGREE OF TOXICITY, INGESTION OF EXCESSIVE QUANTITIES MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT.

COMMENTS:

USED MOTOR OIL IS A POSSIBLE SKIN CANCER HAZARD BASED ON TESTS WITH LABORATORY ANIMALS AND HAS BEEN IDENTIFIED AS A CARCINOGEN BY IARC.

Product Name: UNOCAL GUARDOL MOTOR OIL 30
Product Code No: 03650XX30

Page 3
Issue Date: 05/15/89

SECTION IV - SPECIAL PROTECTION INFORMATION**VENTILATION:**

IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE TO MAINTAIN AIRBORNE CONCENTRATIONS BELOW THE ESTABLISHED EXPOSURE LIMITS (SEE SECTION I), ADDITIONAL VENTILATION OR EXHAUST SYSTEMS MAY BE REQUIRED. WHERE EXPLOSIVE MIXTURES MAY BE PRESENT, ELECTRICAL SYSTEMS SAFE FOR SUCH LOCATIONS MUST BE USED.

RESPIRATORY PROTECTION:

THE USE OF RESPIRATORY PROTECTION IS ADVISED WHEN CONCENTRATIONS EXCEED THE ESTABLISHED EXPOSURE LIMITS (SEE SECTION I). DEPENDING ON THE AIRBORNE CONCENTRATION, USE A RESPIRATOR OR GAS MASK WITH APPROPRIATE CARTRIDGES AND CANNISTERS (NIOSH APPROVED, IF AVAILABLE) OR SUPPLIED AIR EQUIPMENT.

PROTECTIVE GLOVES:

THE USE OF GLOVES IMPERMEABLE TO THE SPECIFIC MATERIAL HANDLED IS ADVISED TO PREVENT SKIN CONTACT AND POSSIBLE IRRITATION.

EYE PROTECTION:

APPROVED EYE PROTECTION TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY IS RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT:

IT IS SUGGESTED THAT A SOURCE OF CLEAN WATER BE AVAILABLE IN THE WORK AREA FOR FLUSHING EYES AND SKIN. IMPERVIOUS CLOTHING SHOULD BE WORN AS NEEDED.

SECTION V - REACTIVITY DATA**STABILITY:**

STABLE UNDER NORMAL CONDITIONS OF STORAGE AND HANDLING.

CONDITIONS TO AVOID (STABILITY):

EXTENDED EXPOSURE TO HIGH TEMPERATURES MAY CAUSE DECOMPOSITION.

INCOMPATIBILITY (MATERIALS TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS:

COMBUSTION MAY YIELD MAJOR AMOUNTS OF OXIDES OF CARBON AND MINOR AMOUNTS OF OXIDES OF SULFUR, NITROGEN, PHOSPHORUS AND ZINC.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

POLYMERIZATION CONDITIONS TO AVOID:

NONE ANTICIPATED

UNION OIL CO.

Product Name: UNOCAL GUARDOL MOTOR OIL 30
Product Code No: 03650XX30

Page 4
Issue Date: 05/15/89

SECTION VI - SPILL AND LEAK PROCEDURES ***HIGHWAY OR RAILWAY SPILLS***
Call CHEMTREC (800) 424-9300 Cont. U.S.
(Collect) (202) 483-7616 from Alaska & Hawaii

PRECAUTIONS IN CASE OF RELEASE OR SPILL:

STAY UPWIND AND AWAY FROM SPILL UNLESS WEARING APPROPRIATE PROTECTIVE EQUIPMENT (SEE SECTION IV). MATERIAL WILL BURN; KEEP ALL SOURCES OF IGNITION AWAY FROM SPILL. COLLECT LEAKING LIQUID IN SEALABLE CONTAINERS. ABSORB SPILLED LIQUID IN SAND OR INERT ABSORBANT. PREVENT SPILLED LIQUID FROM ENTERING SEWERS, STORM DRAINS, OTHER UNAUTHORIZED TREATMENT/DRAINAGE SYSTEMS AND NATURAL WATERWAYS. CONTACT FIRE AUTHORITIES AND APPROPRIATE FEDERAL, STATE OR LOCAL AGENCIES. IF SPILL OF ANY AMOUNT IS MADE INTO OR UPON U.S. NAVIGABLE WATERS, THE CONTIGUOUS ZONE, OR ADJOINING SHORELINES, NOTIFY THE NATIONAL RESPONSE CENTER (PHONE NUMBER 800-424-8802).

REPORTABLE QUANTITY:

NONE

WASTE DISPOSAL METHOD:

DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL REGULATIONS.

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS**HANDLING AND STORAGE PRECAUTIONS:**

STORE IN A COOL, DRY LOCATION. KEEP AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION V). AVOID GENERATING OIL MISTS WHILE HANDLING. AVOID PROLONGED OR REPEATED SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. DO NOT WEAR OIL-SOAKED CLOTHING OR SHOES. FOR USED MOTOR OIL: LAUNDER SATURATED CLOTHING BEFORE WEARING AND DISCARD OIL-SOAKED SHOES AND UNWASHABLE CLOTHING.

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

NFPA	HEALTH HAZARD: 0	HAZARD RANKING	FLASH POINT
HAZARD	FLAMMABILITY: 1	0 = LEAST	
CLASS	REACTIVITY: 0	1 = SLIGHT	
	OTHER:	2 = MODERATE	372F COC
		3 = HIGH	206C COC
		4 = EXTREME	

EXTINGUISHING MEDIA:

EXTINGUISH WITH DRY CHEMICAL, CO2, WATER SPRAY, FOAM, SAND OR EARTH. WATER AND FOAM MAY CAUSE FROTHING.

FIRE & EXPLOSION HAZARDS:

THIS MATERIAL WILL BURN, BUT WILL NOT IGNITE READILY. IF CONTAINER IS NOT PROPERLY COOLED, IT MAY EXPLODE IN HEAT OF A FIRE.

FIRE FIGHTING PROCEDURES:

WATER SPRAY MAY BE USEFUL IN MINIMIZING VAPORS AND COOLING CONTAINERS EXPOSED TO HEAT AND FLAME. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. MOVE UNDAMAGED CONTAINERS FROM FIRE AREA IF IT CAN BE DONE WITHOUT RISK.

Product Name: UNOCAL GUARDOL MOTOR OIL 30
Product Code No: 03650XX30

Page 5
Issue Date: 05/15/89

SECTION IX - PHYSICAL DATA

<u>APPROX BOILING POINT</u>	<u>(AIR = 1) VAPOR DENSITY</u>	<u>(N-BUTYL ACETATE = 1) EVAPORATION RATE</u>	<u>% VOLATILE</u>
>600F / 316C	>1	<1	NEGLIGIBLE
<u>% SOLUBILITY IN WATER</u>	<u>VAPOR PRESSURE</u>	<u>PH</u>	
NEGLIGIBLE	NOT NOTED	NOT NOTED	
<u>SPECIFIC GRAVITY</u>		<u>APPROX. BULK DENSITY (LB/GAL)</u>	
0.89-0.91		NOT NOTED	
<u>APPEARANCE</u>			
CLEAR, BROWN LIQUID			
<u>ODOR</u>			
CHARACTERISTIC			

SECTION X - PRECAUTIONARY LABEL/WARNING

WARNING! USED MOTOR OIL IS A POSSIBLE SKIN CANCER HAZARD BASED ON TESTS WITH LABORATORY ANIMALS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. AVOID PROLONGED OR REPEATED SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, GRIND OR DRILL ON OR NEAR THIS CONTAINER OR EXPOSE TO ANY SOURCE OF IGNITION. "EMPTY" CONTAINER RETAINS RESIDUE (LIQUID AND/OR VAPOR) AND MAY EXPLODE IN HEAT OF A FIRE. FIRST AID: IN CASE OF CONTACT, FLUSH EYES OR SKIN WITH PLENTY OF WATER. IF SWALLOWED, FIRST AID IS NOT NORMALLY REQUIRED.

SECTION XI - DOCUMENTARY INFORMATION

ISSUE DATE: 05/15/89 PRODUCT CODE NO. 03650XX30
PREV. DATE: 01/05/89 PREV. PROD. CODE NO. 03650XX30
MSDS NO: N/A PREV. MSDS NO: N/A

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.

***** THIS IS THE LAST PAGE *****

***** THIS IS THE LAST PAGE *****

***** THIS IS THE LAST PAGE *****